AWO Tankerman Subcommittee: Vessel Access/Egress Best Practices

- 1. Always inspect any means of access prior to use. If something seems wrong, don't use it.
- 2. Confirm means of access is also suitable for quick use in the event of an emergency.
- 3. Only use the access means in the intent it was designed (i.e. do not use a ladder as a gangway).
- 4. Communicate with the dock operator, or other nearby personnel, that you are about to go on/off the vessel. Request that they maintain a visual watch of you for the duration of the task.
- 5. Utilize cranes, baskets, or tag lines to lower/raise equipment rather than carry it while accessing/exiting the vessel.
- 6. Never carry tools or equipment when climbing.
- 7. Wear gloves to protect hands while climbing ladders or transiting gangways.
- 8. Exercise caution when using a gangway or ladder. Think through every step/rung, don't just go through the motions.
- 9. Always face the ladder rungs when climbing, and face into the stairwell when using steep stairs.
- 10. Do not take more than one step at a time when using ladders or gangways.
- 11. When climbing a ladder, always maintain your body positioning so that your belt buckle stays within the side rails.
- 12. Only one person on a gangway or ladder at a time.
- 13. Gangways should be properly secured at both ends.
- 14. Gangways should be placed at a minimum of 36" from the edge of the vessel and dock.
- 15. Periodically adjust gangway placement throughout the transfer, if needed.
- 16. Raise gangway to a safe height when not being used.
- 17. Stop Work Authority/Responsibility/Obligation...whatever you call it, make sure your employees feel empowered to USE IT!